Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

MEAN WELL

SWITCHING POWER SUPPLY

ISO-9001 CERTIFIED MANUFACTURER

S-25 SERIES

Jameco Part Number 123271 (S-25-224)

.LOW COST, HIGH RELIABILITY .COMPACT SIZE, LIGHT WEIGHT
.105◦C OUTPUT CAPACITOR .100% FULL LOAD BURN-IN TEST
.INTERNATIONAL AC INPUT RANGE .BUILT IN EMI FILTER, LOW RIPPLE NOISE
.HIGH EFFICIENCY, LOW WORKING TEMPERATURE
.SOFT-START CIRCUIT, LIMITING AC SURGE CURRENT
.SHORT CIRCUIT, OVERLOAD, OVER VOLTAGE PROTECTED

MODEL / SPECIFICATION	S-25-5	S-25-12	S-25-15	S-25-24
DC OUTPUT VOLTAGE	5V	12V	15V	24V
OUTPUT V. TOLERANCE	±2%	±1%	±1%	±1%
OUTPUT RATED CURRENT	5A	2.1A	1.7A	1.1A
OUTPUT CURRENT RANGE	0-5A	0-2.1A	0-1.7A	0-1.1A
RIPPLE & NOISE	50mVp-p	100mVp-p	100mVp-p	100mVp-p
LINE REGULATION	±0.5%	±0.5%	±0.5%	±0.5%
LOAD REGULATION	±1%	±0.5%	±0.5%	±0.5%
DC OUTPUT POWER	25W	25.2W	25.5W	26.4W
EFFICIENCY	72% / 115VAC	76% / 115VAC	77% / 115VAC	80% / 115VAC
DC VOLTAGE ADJ.	+10,-5%	±10%	±10%	±10%
INPUT VOLTAGE RANGE	85~264VAC 47~63Hz; 120~370VDC			
AC CURRENT	0.6A/115V 0.35A/230V			
INRUSH CURRENT	COLD START 15A/115V 30A/230V			
LEAKAGE CURRENT	<0.75mA/240VAC			
OVERLOAD PROTECTION	105%~150% TYPE:PULSING HICCUP SHUTDOWN RESET:AUTO RECOVERY			
OVER VOLTAGE PROTECTION	115%~135%			
OVER TEMP. PROTECTION	----------			
TEMP. COEFFICIENT	±0.03% / ◦C (0~50◦C)			
SETUP, RISE, HOLD UP TIME	800ms, 50ms, 10ms / 115VAC 300ms, 50ms, 80ms / 230VAC			
VIBRATION	10~500Hz, 2G 10min./1cycle, PERIOD FOR 60min. EACH AXES			
WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC			
ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:500VDC / 100M Ohms			
WORKING TEMP., HUMIDITY	-10◦C~+60◦C(REFER TO OUTPUT DERATING CURVE), 20%~90% RH			
STORAGE TEMP., HUMIDITY	-20◦C~+85◦C, 10%~95% RH			
DIMENSION	99*97*35mm CASE:905			
WEIGHT	0.37Kgs			
SAFETY STANDARDS	UL1012, TUV EN60950 (IEC950, UL1950) APPROVED			
EMC STANDARDS	CISPR22 (EN55022), IEC801-2,3,4, IEC555-2 VERIFICATION			

NOTE :
1.ALL PARAMETERS ARE SPECIFIED AT 230VAC INPUT, RATED LOAD, 25◦C 70% RH. AMBIENT.
2.TOLERANCE G INCLUDE SET UP TOLERANCE, LINE REGULATION, LOAD REGULATION.
3.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR.
4.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.
5.LOAD REGULATION IS MEASURED FROM 0% TO 100% RATED LOAD.
6.C6 MUST BE REMOVED.

JUN.09.98

BLOCK DIAGRAM



fosc: 56KHz

OUTPUT DERATING



STATIC CHARACTERISTICS



DIMENSION (mm)

- CASE : 905
- TERMINAL PIN NO. ASSIGNMENT
  - PIN 1 : DC OUTPUT -V
  - PIN 2 : DC OUTPUT +V
  - PIN 3 : FG ⏚
  - PIN 4,5 : AC INPUT